

# SPECIFICATION SHEET



# SPECIFICATIONS

| VOLTAGE               | 12V AC                                |  |
|-----------------------|---------------------------------------|--|
| POWER CONSUMPTION     | 7W                                    |  |
| LUMEN OUTPUT          | 450 Lumens                            |  |
| OPERATING FREQUENCY   | 50 / 60Hz                             |  |
| сст                   | 2700K/3000K/4000K                     |  |
| CRI                   | 80+                                   |  |
| DIMMING               | YES                                   |  |
| FINISH                | Antique Bronze                        |  |
| IP RATING             | IP65 wet location                     |  |
| OPERATING TEMPERATURE | -4 ~ 122°F (-20 ~ 50°C)               |  |
| AMBIENT TEMPERATURE   | -4 ~ 176°F (-20 ~ 80°C)               |  |
| LUMEN MAINTENANCE     | 50,000 hrs.                           |  |
| MOUNTING              | 10" Hammer stake with cutout for wire |  |
| LENS                  | Clear flat glass                      |  |
| OPTICS                | 35° flood / 60° wide flood            |  |
|                       |                                       |  |


| JOB NAME:   |  |
|-------------|--|
| LOCATION:   |  |
| QUOTE/REF#: |  |

The BFL-501 is a professional and architectural grade spotlight with an integrated LED suitable for uplighting applications. Its heavy, solid cast brass body featuers a sleek and modern design which also acts as a heat sink allowing the fixture to operate at a much cooler temperature. Outdoor rated, waterproof.

## FEATURES

- Solid Brass contstruction.
- Antique Bronze finish.
- High performance CREE LED's
- 450 Lumens
- Available in 27K / 30K / 40K
- Dimmable
- IP65 Outdoor / Wet Rated
- ETL LISTED

# DIMENSIONS





### ORDERING GUIDE EX: BFL-501-AB-30K-35-12V

| BFL-501-AB |  |                                    |                     |
|------------|--|------------------------------------|---------------------|
| MODEL      | COLOR TEMPERATURE  | BEAM ANGLE                         | VOLTAGE             |
|            | <b>27K</b> - 2700K<br><b>30K</b> - 3000K<br><b>40K</b> - 4000K | <b>35</b> - 35°<br><b>60</b> - 60° | <b>12V</b> - 12V DC |