

SPECIFICATION SHEET



SPECIFICATIONS

VOLTAGE 12V POWER CONSUMPTION 7W LUMEN OUTPUT 450 Lumens OPERATING FREQUENCY 50 / 60Hz CCT 4000K CRI 80+ DIMMING YES FINISH Antique Bronze IP RATING IP65 wet location OPERATING TEMPERATURE -4 ~ 122°F (-20 ~ 50°C) AMBIENT TEMPERATURE -4 ~ 176°F (-20 ~ 80°C) LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass OPTICS 35° flood / 60° wide flood		
LUMEN OUTPUT 450 Lumens OPERATING FREQUENCY 50 / 60Hz CCT 4000K CRI 80+ DIMMING YES FINISH Antique Bronze IP RATING IP65 wet location OPERATING TEMPERATURE -4 ~ 122°F (-20 ~ 50°C) AMBIENT TEMPERATURE -4 ~ 176°F (-20 ~ 80°C) LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	VOLTAGE	12V
OPERATING FREQUENCY 50 / 60Hz CCT 4000K CRI 80+ DIMMING YES FINISH Antique Bronze IP RATING IP65 wet location OPERATING TEMPERATURE -4 ~ 122°F (-20 ~ 50°C) AMBIENT TEMPERATURE -4 ~ 176°F (-20 ~ 80°C) LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	POWER CONSUMPTION	7W
CCT 4000K CRI 80+ DIMMING YES FINISH Antique Bronze IP RATING IP65 wet location OPERATING TEMPERATURE -4 ~ 122°F (-20 ~ 50°C) AMBIENT TEMPERATURE -4 ~ 176°F (-20 ~ 80°C) LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	LUMEN OUTPUT	450 Lumens
CRI 80+ DIMMING YES FINISH Antique Bronze IP RATING IP65 wet location OPERATING TEMPERATURE -4 ~ 122°F (-20 ~ 50°C) AMBIENT TEMPERATURE -4 ~ 176°F (-20 ~ 80°C) LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	OPERATING FREQUENCY	50 / 60Hz
DIMMING YES FINISH Antique Bronze IP RATING IP65 wet location OPERATING TEMPERATURE -4 ~ 122°F (-20 ~ 50°C) AMBIENT TEMPERATURE -4 ~ 176°F (-20 ~ 80°C) LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	сст	4000K
FINISH Antique Bronze IP RATING IP65 wet location OPERATING TEMPERATURE -4 ~ 122°F (-20 ~ 50°C) AMBIENT TEMPERATURE -4 ~ 176°F (-20 ~ 80°C) LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	CRI	80+
IP RATING IP65 wet location OPERATING TEMPERATURE -4 ~ 122°F (-20 ~ 50°C) AMBIENT TEMPERATURE -4 ~ 176°F (-20 ~ 80°C) LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	DIMMING	YES
OPERATING TEMPERATURE $-4 \sim 122^{\circ}\text{F} \ (-20 \sim 50^{\circ}\text{C})$ AMBIENT TEMPERATURE $-4 \sim 176^{\circ}\text{F} \ (-20 \sim 80^{\circ}\text{C})$ LUMEN MAINTENANCE $50,000 \text{ hrs.}$ MOUNTING 10° Hammer stake with cutout for wire LENS Clear flat glass	FINISH	Antique Bronze
AMBIENT TEMPERATURE -4 ~ 176°F (-20 ~ 80°C) LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	IP RATING	IP65 wet location
LUMEN MAINTENANCE 50,000 hrs. MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	OPERATING TEMPERATURE	-4 ~ 122°F (-20 ~ 50°C)
MOUNTING 10" Hammer stake with cutout for wire LENS Clear flat glass	AMBIENT TEMPERATURE	-4 ~ 176°F (-20 ~ 80°C)
LENS Clear flat glass	LUMEN MAINTENANCE	50,000 hrs.
	MOUNTING	10" Hammer stake with cutout for wire
OPTICS 35° flood / 60° wide flood	LENS	Clear flat glass
	OPTICS	35° flood / 60° wide flood




The BFL-501 is a professional and architectural grade spotlight with an integrated LED suitable for uplighting applications. Its heavy, solid cast brass body featuers a sleek and modern design which also acts as a heat sink allowing the fixture to operate at a much cooler temperature. Outdoor rated, waterproof.

FEATURES

- Solid Brass contstruction.
- Antique Bronze finish.
- High performance CREE LED's
- 450 Lumens
- Available in 40K
- Dimmable
- IP65 Outdoor / Wet Rated
- ETL LISTED
- MOUNTING STAKE INCLUDED WITH EVERY **FIXTURE**

DIMENSIONS

















ORDERING GUIDE EX: BFL-501-AB-30K-35-12V

BFL-501-AB			
MODEL	COLOR TEMPERATURE	BEAM ANGLE	VOLTAGE
	40K - 4000K	35 - 35° 60 - 60°	12V - 12V DC